



RAIN SCREEN TAPE

1. DESCRIPTION

Polyguard Rain Screen Tape is designed to cover joints of dissimilarly shaped products in the **Polyguard Rain Screen** product line.

2. LIMITATIONS

None when used for the design purpose.

3. MATERIALS AND COMPOSITION

Stabilized plasticized PVC film coated with a non-corrosive pressure-sensitive adhesive.

4. PHYSICAL PROPERTIES

Width:	6-inches
Length:	55 yards / 165 feet
Total Thickness:	2.0 mils (0.048mm)
Backing	Polypropylene
Tensile Strength:	16 lb./in. (31.5/10mm)
Elongation at Break:	≤180%
Color:	Black
Temperature Range	32°F to 140°F

5. CHEMICAL RESISTANCE

Not reactive to common building materials.

6. TECHNICAL DATA

Polyguard Products, Inc. provides design data and installation instructions to architects, engineers, specifiers, and contractors.

7. INSTALLATION:

Storage: Protect the material from heat, crushing, moisture, mud, and construction dirt. Keep the product in the package until it will be used.

Safety: Material Safety Data Sheets are available upon request by phone, e-mail, or on the web.

Installation Instructions:

Apply to clean and dry surfaces.

8. AVAILABILITY AND COST:

Packaged 12 rolls per carton.

Information about a distributor near you is available upon request by phone or e-mail.

9. GUARANTEE:

The **Polyguard Rain Screen Tape** will meet published specifications at the time of delivery.

10. TECHNICAL SERVICES:

Polyguard Products, Inc. offers specialist advice to aid the architect, engineer, and contractor with the management of moisture and air in exterior wall assemblies.

© Polyguard Products 2010

X:/Lit/Arch/Rain Screen Vinyl Tape.doc R.8-5-10