

POLYGUARD UNDERSEAL FABRIC TAPE

DESCRIPTION:

POLYGUARD UNDERSEAL™ FABRIC TAPE is a rubberized asphalt waterproofing membrane laminated to polypropylene fabric backing. The membrane is wound onto a disposable silicone treated release sheet to prevent the membrane from sticking onto itself while in the roll.

TYPICAL USES:

POLYGUARD UNDERSEAL™ FABRIC TAPE is used around pipe penetrations with a annular space of pipe through opening exceeding ½", endlaps and for patching damaged areas of the **POLYGUARD UNDERSEAL™BLINDSIDE and UNDERSLAB** waterproofing membranes.

LIMITATIONS:

Material is UV resistant and exposure should not exceed 30 days.

PACKAGING:

Supplied in rolls 12" x 200' (1 roll per carton)

TECHNICAL DATA:

TYPICAL PROPERTIES	TYPICAL VALUES	TEST METHOD
Thickness	65 mils	
Tensile Strength	50 lbs./in. Width (769 PSI)	ASTM D 882 (Method B)
Puncture Resistance	200 lbs.	ASTM E 154
Permeance – Perms	0.1 max	ASTM E 96 (Method B)
Pliability at low temperatures (0°F., -15°F., -25°F)*	No cracks in fabric or rubberized asphalt	ASTM D 146 (Modified)
Elongation	80	ASTM D 4632
Grab Tensile Strength	246	ASTM D 4632

INSTALLATION:

POLYGUARD UNDERSEAL™ BLINDSIDE and UNDERSLAB waterproofing membrane should be clean, dry and free of contaminates before application of the **POLYGUARD UNDERSEAL™ FABRIC TAPE**. Apply the **POLYGUARD 650 LT LIQUID ADHESIVE** or **CALIFORNIA SEALANT** at a rate of 150-200 sq. ft. per gallon to the **POLYGUARD UNDERSEAL™ BLINDSIDE** or **UNDERSEAL** prior to applying the **POLYGUARD UNDERSEAL™ FABRIC TAPE**.

Underseal™ is protected by U.S. Patent No. 7,488,523

Polyguard

This Information is based on our best knowledge, but POLYGUARD cannot guarantee the results to be obtained.

POLYGUARD PRODUCTS, INC • ENNIS, TEXAS 75120-0755
PH: 214-515-5000 • 800-541-4994 • FAX: 972-875-9425
Web Site: www.polyguardproducts.com

ISO 9001
BUREAU VERITAS
Certification



Polyguard has been ISO 9000 certified since 1996. Current certifications are:
- American Natl. Standards Institute
- Dutch Council for Certification
- Deutscher Akkreditierungs Rat

Due to various uses of this product please see sheet membrane to be used for proper applications instructions.

MATERIAL SAFETY DATA:

All Material Safety Data Sheets and precautionary labels should be using. Consult **POLYGUARD PRODUCTS, INC.** Material Safety Data Sheets and OSHA regulations for additional safety and health information for the products described herein. Purchaser is responsible for complying with all applicable federal, state or local laws and regulations covering use of the product including waste disposal.

LIMITED WARRANTY:

This material is offered for sale by **POLYGUARD PRODUCTS, INC.** only for the expressed purposes as described in this literature. Any use of the products described in this literature for purposes other than taught therein by **POLYGUARD PRODUCTS, INC.** shall be the responsibility of the purchaser and **POLYGUARD PRODUCTS, INC.** does not warrant nor will be responsible for any misuse of these products. **POLYGUARD PRODUCTS, INC.** will replace **F.O.B.** Ennis, Texas, material not meeting our manufacturer's specification one year from date of sale.

POLYGUARD products as described herein are for industrial use only. The application procedures should be performed by workmen who are skilled in the application of material described herein accordance with manufacturer specifications.