



## TERMINATION BAR

### TECHNICAL DESCRIPTION:

**POLYGUARD TERMINATION BAR** is a high strength vinyl/plastic strip designed to support vertical membrane systems at their termination points. The term bar is intended for attaching and sealing **Polyguard Products** waterproofing products, drainage boards and flashing systems to the substrate.

### PHYSICAL DATA:

Size	Rolls or Sticks per Ctn	Weight
1" x 50'	4 Coils per ctn - 200 L.F.	28 lbs
1" x 10'	25 strips per ctn - 250 L.F.	28 lbs

### INSTALLATION:

Surface should be clean, dry and free of contaminants. Install **POLYGUARD TERMINATION BAR** at the top edge of material that it is to be supported. When applying make sure that the grooves on back of term bar are facing up. This allows for the term bar to grip the membrane. Fasten into substrate using pre-drilled holes every 8" O.C with appropriate mechanical or power actuated fasteners. Apply a bead of **Polyguard 650 Mastic** to top of termination bar after application is complete.

### LIMITED WARRANTY:

This material is offered for sale by **POLYGUARD PRODUCTS, INC.** only for the expressed purposes as described in this literature. Any use of the products described in this literature for purposes other than taught therein by **POLYGUARD PRODUCTS, INC.** shall be the responsibility of the purchaser and **POLYGUARD PRODUCTS, INC.** does not warrant nor will be responsible for any misuse of these products. **POLYGUARD PRODUCTS, INC.** will replace **E.X.W.** Ennis, Texas, material not meeting our manufacturer's specification one year from date of sale.

**POLYGUARD** products as described herein are for industrial use only. The application procedures should be performed by workmen who are skilled in the application of material described herein in accordance with manufacturer specifications.

This product is not covered by **POLYGUARD** Products ISO 9001 certification.

X:/lit/arch/2011/Termination Bar.doc R1-22-08