

Material Safety Data Sheet

LM 95 Part A

1. Product and company identification

Product name	: LM 95 Part A
Material uses	: Used as a two part urethane waterproofing.
Supplier/Manufacturer	: Polyguard Products 3801 South Business 45 Ennis, TX 75119 Tel: (800)541-4994
Responsible name	: Atrion Regulatory Services, Inc.
In case of emergency	: CHEMTREC, U.S. : +1-800-424-9300 International: +1-703-527-3887

2. Hazards identification

Physical state	: Liquid.
Odor	: Asphalt.
OSHA/HCS status	: While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this MSDS contains valuable information critical to the safe handling and proper use of the product. This MSDS should be retained and available for employees and other users of this product.
Emergency overview	: MAY CAUSE RESPIRATORY TRACT AND EYE IRRITATION. Avoid breathing vapor or mist. Avoid contact with eyes. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.
Potential acute health effects	
Inhalation	: Slightly irritating to the respiratory system.
Ingestion	: No known significant effects or critical hazards.
Skin	: No known significant effects or critical hazards.
Eyes	: Slightly irritating to the eyes.
Potential chronic health effects	
Chronic effects	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.
Over-exposure signs/symptoms	
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Ingestion	: No specific data.
Skin	: No specific data.
Eyes	: Adverse symptoms may include the following: irritation watering redness
Medical conditions aggravated by over-exposure	: None known.
See toxicological information (section 11)	

3 . Composition/information on ingredients

United States

Name	CAS number	%
Limestone	1317-65-3	30 - 60
Asphalt	8052-42-4	30 - 60

Canada

Name	CAS number	%
Limestone	1317-65-3	30 - 60
Asphalt	8052-42-4	30 - 60

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4 . First aid measures

- Eye contact** : Check for and remove any contact lenses. In case of contact with eyes, rinse immediately with plenty of water. Get medical attention if symptoms occur.
- Skin contact** : Wash with soap and water. Get medical attention if symptoms occur.
- Inhalation** : If inhaled, remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms appear.
- Ingestion** : Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention if symptoms appear.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.
- Notes to physician** : No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

5 . Fire-fighting measures

- Flammability of the product** : May be combustible at high temperature.
- Extinguishing media**
 - Suitable** : Use dry chemical, CO₂, water spray (fog) or foam.
 - Not suitable** : None known.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
metal oxide/oxides
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6 . Accidental release measures

- Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6 . Accidental release measures

Methods for cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

7 . Handling and storage

- Handling** : Put on appropriate personal protective equipment (see section 8). Do not breathe vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
- Storage** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8 . Exposure controls/personal protection

United States

Product name

Limestone

Exposure limits

NIOSH REL (United States, 12/2001).

TWA: 5 mg/m³ 10 hour(s). Form: Respirable fractionTWA: 10 mg/m³ 10 hour(s). Form: Total

OSHA PEL (United States, 11/2006).

TWA: 5 mg/m³ 8 hour(s). Form: Respirable fractionTWA: 15 mg/m³ 8 hour(s). Form: Total dust

Asphalt

ACGIH TLV (United States, 1/2007).

TWA: 0.5 mg/m³ 8 hour(s). Form: Fume

NIOSH REL (United States, 12/2001).

CEIL: 5 mg/m³ 15 minute(s). Form: Fume

Canada

Product name

Limestone

Exposure limits

CA Alberta Provincial (Canada, 10/2006).

8 hrs OEL: 10 mg/m³ 8 hour(s).

CA British Columbia Provincial (Canada, 7/2007).

TWA: 10 mg/m³ 8 hour(s). Form: Total dustSTEL: 20 mg/m³ 15 minute(s).TWA: 3 mg/m³ 8 hour(s). Form: Respirable dust

CA Ontario Provincial (Canada, 3/2007).

TWA: 10 mg/m³ 8 hour(s). Form: total dust

CA Quebec Provincial (Canada, 12/2006).

TWA: 10 mg/m³ 8 hour(s). Form: Total dust.

Asphalt

CA Alberta Provincial (Canada, 10/2006).

8 hrs OEL: 5 mg/m³ 8 hour(s). Form: Fume

8 . Exposure controls/personal protection

8 hrs OEL: 5 mg/m³ 8 hour(s).

CA British Columbia Provincial (Canada, 7/2007).

TWA: 0.5 mg/m³, (as benzene-soluble aerosol) 8 hour(s). Form:
Inhalable fume




CA Ontario Provincial (Canada, 3/2007).

TWAEV: 0.5 mg/m³, (benzene soluble aerosol) 8 hour(s).

CA Quebec Provincial (Canada, 12/2006).

TWAEV: 5 mg/m³ 8 hour(s). Form: fume

Consult local authorities for acceptable exposure limits.

- Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.
- Engineering measures** : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Personal protection**
- Eyes** : Safety glasses.
- Skin** : Overalls buttoned to the neck and wrist.
- Respiratory** : A respirator is not needed under normal and intended conditions of use.
- Hands** : Chemical resistant gloves.
- Personal protective equipment (Pictograms)** :
- 


- HMIS Code/Personal protective equipment** : B
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9 . Physical and chemical properties

- Physical state** : Liquid.
- Flash point** : Open cup: 274°C (525.2°F) [Cleveland.]
- Auto-ignition temperature** : 485°C (905°F)
- Color** : Black.
- Odor** : Asphalt.
- Specific gravity** : 1.29
- VOC** : 0 (g/l).
- Solubility** : Partially soluble in the following materials: cold water and hot water.

10 . Stability and reactivity

- Stability** : The product is stable.
- Hazardous polymerization** : Under normal conditions of storage and use, hazardous polymerization will not occur.
- Conditions to avoid** : Avoid all possible sources of ignition (spark or flame).
Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Do not allow vapor to accumulate in low or confined areas.
- Materials to avoid** : Reactive or incompatible with the following materials: oxidizing materials and acids.
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11 . Toxicological information

Acute toxicity

- Inhalation** : Slightly irritating to the respiratory system.
- Ingestion** : No known significant effects or critical hazards.
- Skin** : No known significant effects or critical hazards.
- Eyes** : Slightly irritating to the eyes.

Carcinogenicity

Classification

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
Asphalt	A4	3	-	+	-	-

12 . Ecological information

- Environmental effects** : No known significant effects or critical hazards.

13 . Disposal considerations

- Waste disposal** : The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14 . Transport information

Regulatory information

- DOT/ TDG / IMDG/ IATA** : Not regulated.

15 . Regulatory information

United States

- HCS Classification** : Not regulated.
- U.S. Federal regulations** : TSCA 8(a) PAIR: Amorphous silica; 1-Cyclohexene, 4-vinyl-
United States inventory (TSCA 8b): All components are listed or exempted.
SARA 302/304/311/312 extremely hazardous substances: No products were found.
SARA 302/304 emergency planning and notification: No products were found.
SARA 302/304/311/312 hazardous chemicals: Limestone; Asphalt
SARA 311/312 MSDS distribution - chemical inventory - hazard identification
 Limestone: Immediate (acute) health hazard; Asphalt: Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard
Clean Water Act (CWA) 307: No products were found.
Clean Water Act (CWA) 311: No products were found.
Clean Air Act (CAA) 112 accidental release prevention 1,3-Butadiene
Clean Air Act (CAA) 112 regulated flammable substances 1,3-Butadiene
Clean Air Act (CAA) 112 regulated toxic substances No products were found.

State regulations

- Connecticut Carcinogen Reporting**: None of the components are listed.
Connecticut Hazardous Material Survey: None of the components are listed.
Florida substances: None of the components are listed.
Illinois Chemical Safety Act None of the components are listed.
Illinois Toxic Substances Disclosure to Employee Act None of the components are listed.
Louisiana Reporting: None of the components are listed.
Louisiana Spill: None of the components are listed.
Massachusetts Spill: None of the components are listed.
Massachusetts Substances: The following components are listed: Limestone;Asphalt
Michigan Critical Material: None of the components are listed.
Minnesota Hazardous Substances: None of the components are listed.
New Jersey Hazardous Substances: The following components are listed: Asphalt
New Jersey Spill: None of the components are listed.
New Jersey Toxic Catastrophe Prevention Act: None of the components are listed.
New York Acutely Hazardous Substances: None of the components are listed.
New York Toxic Chemical Release Reporting: None of the components are listed.
Pennsylvania RTK Hazardous Substances: The following components are listed:
 Limestone; Asphalt;Dipropylene glycol
Rhode Island Hazardous Substances: None of the components are listed.

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

Ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
1,3-Butadiene	Yes.	Yes.	Yes.	No.
1-Cyclohexene, 4-vinyl-	Yes.	No.	No.	No.

Canada

- WHMIS (Canada)** : Not controlled under WHMIS (Canada).

Canadian lists

- CEPA Toxic substances**: None of the components are listed.
Canadian ARET: None of the components are listed.
Canadian NPRI: None of the components are listed.
Alberta Designated Substances: None of the components are listed.
Ontario Designated Substances: None of the components are listed.
Quebec Designated Substances: None of the components are listed.

Canada inventory

- Canada inventory**: At least one component is not listed in DSL but all such components are listed in NDSL.

15 . Regulatory information

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

International regulations

International lists : This product, (and its ingredients) is (are) listed on national inventories, or is (are) exempted from being listed, in Australia (AICS), in Europe (EINECS/ELINCS), in Korea (TCCL), in Japan (METI), in the Philippines (RA6969).

16 . Other information

Label requirements : MAY CAUSE RESPIRATORY TRACT AND EYE IRRITATION.

Hazardous Material Information System (U.S.A.) :


HAZARD RATINGS

Health	1
Fire hazard	1
Physical Hazard	0
Personal protection	B

4- Extreme
3- Serious
2- Moderate
1- Slight
0- Minimal
See section 8 for more detailed information on personal protection.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.) :



References : ANSI Z400.5, MSDS Standard, 2004. - Manufacturer's Material Safety Data Sheet. - 29CFR Part1910.1200 OSHA MSDS Requirements. - 49CFR Table List of Hazardous Materials, UN#, Proper Shipping Names, PG. - Canada Gazette Part II, Vol. 122, No. 2. Registration SOR/88-64, 31 December 1987. Hazardous Products Act "Ingredient Disclosure List" - Canadian Transport of Dangerous Goods, Regulations and Schedules, Clear Language version 2005.

Date of issue : 07/15/2008

Version : 1

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.