

POLYGUARD WEIGHT SCALE TAPE

DESCRIPTION:

POLYGUARD WEIGHT SCALE TAPE comprises a rubberized asphalt waterproofing element and a polypropylene mesh laminated to the outer surface. The total laminated thickness is sixty-five mils. The tape is wound on a disposable release treated strip sheet to prevent blocking in the roll.

USES:

WEIGHT SCALE TAPE is applied to pavement surfaces in order to secure, on a temporary basis, weight scales or traffic counter hoses.

No other use of these materials is to be made without prior approval of **POLYGUARD** as to service and method of application.

TECHNICAL DATA		
PROPERTY	TYPICAL MEASUREMENT	TEST METHOD
Total Thickness	50 mils Minimum	
Tensile Strength - Mesh	80 lb/in	ASTM D 882 (Modified for 1" opening)
Puncture Resistance - Mesh	200 lbs.	ASTM E 154
Pliability - 1/4" Mandrel	No cracks in mesh or rubberized asphalt	ASTM D 146 180°F. bend @ 0°F.
Permeance (perms)	0.1 max	ASTM E 96 Method B (Modified)
POLYGUARD WEIGHT SCALE TAPE 200' rolls	4" width: 3 per carton, 80 lbs/carton, 200 ft ² /carton. 6" width: 2 per carton, 80 lbs/carton, 200 ft ² /carton. 8" width: 1 per carton, 54 lbs/carton, 133 ft ² /carton. 12" width: 1 per carton, 80 lbs/carton, 200 ft ² /carton.	

PRECAUTIONS:

WEIGHT SCALE TAPE should be applied only to pavement which is clean, dry, smooth, and free of debris. Temperature should be over 45°F.

POLYGUARD 650 LIQUID ADHESIVE is to be used with **WEIGHT SCALE TAPE**. Contact **POLYGUARD** for **650 LIQUID ADHESIVE** recommendations.



This Information is based on our best knowledge, but POLYGUARD cannot guarantee the results to be obtained.

POLYGUARD PRODUCTS, INC • ENNIS, TEXAS 75120-0755
 PH: 214-515-5000 • 800-541-4994 • FAX: 972-875-9425
 Web Site: www.polyguardproducts.com



Polyguard has been ISO 9000 certified since 1995. Current certifications are:
 - American Natl. Standards Institute
 - Dutch Council for Certification
 - Deutscher Akkreditierungs Rat

This material is offered for sale by **POLYGUARD PRODUCTS, INC.**, only for the expressed purpose as described in this literature for purposes other than taught therein by **POLYGUARD PRODUCTS, INC.** shall be the responsibility of the purchaser and **POLYGUARD PRODUCTS, INC.** does not warrant nor will be responsible for any misuse of these products. **POLYGUARD PRODUCTS, INC.** will replace, F.O.B. Ennis, TX., materials not meeting our manufacturers' specifications, one year from date of sale.

POLYGUARD products as described herein are for industrial use only. The application of these products should be performed by workmen who are skilled in the application of materials described herein in accordance with manufacturers' specifications.

MATERIAL SAFETY DATA:

All Material Safety Data Sheets and precautionary labels should be read and understood by all user supervisory personnel and employees before using. Consult **POLYGUARD PRODUCTS, INC.**, Material Safety Data Sheets and OSHA regulations for additional safety and health information for the products described herein. Purchaser is responsible for complying with all applicable federal, state, or local laws and regulations covering use of the product including waste and disposal.

This is not a Material Safety Data Sheet and is not to be used as such. **POLYGUARD** has prepared separate Material Safety Data Sheets on each product.

MAINTENANCE:

Not required.

TECHNICAL SERVICE:

Assistance and information is available from any **POLYGUARD** distributor or dealer, or contact us at our Ennis, TX office.