

# RG-2400<sup>®</sup> CLEANER

**RG-2400<sup>®</sup> Cleaner** is a low V.O.C., fast-acting, readily biodegradable cleaner which lifts heavy grease, oil, synthetic oil, and preservatives. Cleans accumulated cutting fluids and petroleum residues. Developed to remove and clean up the RG-2400<sup>®</sup> corrosion gels. Biodegradable, non-petroleum, high flash point, low V.O.C., maximum strength formulation is ready-to-use. Clean up any residue with soap and water.

<u>TEST METHOD</u>	<u>DESCRIPTION</u>	<u>RESULTS</u>
ASTM E-659	Autoignition Temperature	253°C
	Ignition Delay Time	136.5 seconds
	Barometric Pressure	757 mm Hg
ASTM D-92	Flash Point & Fire Point	245°F*
	*occurred simultaneously	
ASTM D-93	Flash Point	184°F
ASTM D-1218	Refractive Index	1.45775 @ 25°C
ASTM D-1120	Boiling Point	528°F @ 761 mm Hg
ASTM D-1177	Freezing Point	No Distinct Inflections
ASTM D-2879	Vapor Pressure @ 25°C	1.8 mm Hg
ASTM D-1298	Specific Gravity	29.2 @ 60°F

Ingredients are E.P.A. listed as approved replacement chemical for solvent usage.

DISPOSE OF CLEANING RESIDUES IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL LAWS AND REGULATIONS.

## Polyguard

PO Box 755, Ennis, TX 75120  
TELE: (214)515-5000 FAX (972) 875-9425  
[www.rq2400.com](http://www.rq2400.com)



*The information given here is considered to be correct and is offered for your consideration, investigation and verification. No warranties are expressed or implied since the use of our products is beyond our control. Statements concerning the use of Polyguard Products are not to be construed as recommending the infringement of any patent*      *Revision Date: 2-15-07*