

RG FAMILY OF PRODUCTS—OVERVIEW

RG-2400 LT

- CONSIDERED OUR 'STANDARD' PRODUCT— APPLIED TO 98% OF SYSTEMS
- FORMULATED TO BE APPLIED TO COLD PIPES
- FOR USE ON ANY SYSTEM UP TO 250°F
- AMMONIA SYSTEMS, BRINE SYSTEMS, GLYCOL SYSTEMS, LNG, CRYOGENIC
- EXCELLENT FOR WELD PACKS ON PRE-INSULATED PIPE SYSTEMS
- LOW PRESSURE STEAM



RG-2400 NP

- FORMULATED TO BE APPLIED TO NEW PIPING SYSTEMS
- FOR USE ON ANY SYSTEM UP TO 230°F
- AMMONIA SYSTEMS, BRINE SYSTEMS, GLYCOL SYSTEMS, LNG, CRYOGENIC



RG-2400 ET

- OUR 'ELEVATED TEMPERATURE' PRODUCT
- FORMULATED TO BE APPLIED SYSTEMS UP TO 350°F
- EXCELLENT FOR WELD PACKS ON PRE-INSULATED PIPE SYSTEMS
- FOR USE ON ANY SYSTEM UP TO 350°F
- LOW TO HIGH PRESSURE STEAM
- GLOVE OR SPRAY APPLICATION



RG-2400 AK

- FORMULATED TO BE APPLIED TO HOT IN SERVICE PIPES UP TO 200°F
- BECOMES THICK BELOW 100°F
- FOR USE ON ANY HOT SYSTEM UP TO 250°F
- GLOVE APPLICATION



RG-CHW

- FORMULATED TO BE APPLIED TO CHILLED WATER SYSTEMS ONLY
- TEMPERATURE RANGE OF ONLY 40°F—140°F
- GLOVE OR SPRAY APPLICATION
- DESIGNED AS AN AFFORDABLE PRODUCT FOR CHILLED WATER PIPING



RG-2401

- CUSTOM DESIGNED CORROSION CONTROL FOR WELL CASINGS
- FORMULATED TO DISPLACE WATER IN WELLS WITH SERVICE UP TO 250°F
- SPECIAL APPLICATION METHODS MUST BE USED—A PUMPABLE PRODUCT



X:/PGP/Mktg/Lit/Mechanical/2019/RG-2400 Products Overview.doc R6-11-19